



Description: ÖLFLEX CRANE 2S 20 G 1,5_

Lapp code: Lapp 0027505

The **Test voltage** of the cable Lapp 0027505 is 3000 V.

Application range

- For connecting movable control panels and consoles
- As a self-supporting shaft cable; in high rack systems
- Suitable for outdoor applications
- Do not use for lift applications!
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3

Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Special textile wrapping to improve sliding movement between the sheath and cores
- Special PVC-based outer sheath
- Opposing, integrated steel supporting elements

In our Cable list on next page you can find all interesting information acc. article Lapp 0027505 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Cable Ø (mm)	Distance between strain wires (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE 2S						
ÖLFLEX CRANE 2S 8 G 1,5	Lapp 0027503	8 G 1,5	14.7	20	115.0	372.5
ÖLFLEX CRANE 2S 12 G 1,5	Lapp 0027504	12 G 1,5	16.2	21	172.8	439
ÖLFLEX CRANE 2S 20 G 1,5	Lapp 0027505	20 G 1,5	20.1	25	288.0	674