



10/100/1000Mbps Copper Gigabit PCI Card for PC

The D-Link DGE-528T is a high-performance 10/100/1000Mbps copper Gigabit PCI card for desktop PC. Installable in a PC equipped with PCI expansion slots, this card turns a desktop computer into a high-bandwidth Gigabit workstation or a server running at 2000Mbps full-duplex speed.

High-performance Gigabit Speed

Capable of running at full-duplex Gigabit speed, this card gives your PC 2000Mbps data transmission on your existing Cat. 5 twisted-pair network cable. As an inexpensive alternative solution to fiber-optic, the card allows you to instantly upgrade to Gigabit without requiring you to install new, expensive fiber cables. The card supports 10/100/1000Mbps network speed auto-sensing and full/half duplex auto-negotiation.

VLAN to Improve Performance and Security

The card provides on-board screening of VLANs Tagged Ethernet frames, allowing your PC to be configured with a VLAN-supported switch. Your PC can be part of a VLAN network, where domains are segmented up to enhance performance and security.

Wake-On-LAN for Power Management

Wake-On-LAN (WOL) is an Advanced Configuration Power Interface (ACPI) function allowing a powered OFF computer

to be powered ON from a remote station. This function allows the administrator to send wake-up signals to a computer. The WOL function provides a great utility for power management of the PC and allows users to initiate action at irregular times and from distant locations.

Flow Control to Minimize Packet Loss

The card's embedded flow control and independent FIFO provide a means to protect against possible data loss during transmission on the network. When connected to a Gigabit switch supporting flow control, the card receives signals from the switch regarding buffer overrun during peak usage periods. The card then delays transmission until the switch is ready again to accept new data.

Small Form Factor, Lower Power Requirement

Using a single chip solution, this card is very small in size and consumes very little power of your computer system.

Features

- Copper Gigabit connection for PC
- 32-bit 33/66MHz clock speed PCI Bus Master operation
- Built-in 72K FIFO buffer to reduce overhead of memory transfers
- 802.3x Flow Control, auto MDI/MDIX support
- Supports ACPI 2.0 WOL power management
- Supports 802.1Q VLAN Tagging, 802.1p Priority Queues
- Supports up to 7KBytes jumbo frames
- Cable Diagnostics Utility provided
- Optional Remote Boot ROM
- Runs Win98, 2000, ME, NT, XP, XP 64 Edition, Server 2003, NetWare, Linux, MacOS
- Very small size, very low power consumption

DGE-528T

Technical Specifications

10/100/1000Mbps PCI Card

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation
- PCI local bus 2.3 specifications
- IEEE 802.3x Flow Control
- IEEE 802.1Q VLAN Tagging
- IEEE 802.1P Priority Queues

Protocol

CSMA/CD

Data Transfer Rates

- Ethernet: 10Mbps (half duplex)
20Mbps (full duplex)
- Fast Ethernet:
100Mbps (half duplex)
200Mbps (full duplex)
- Gigabit Ethernet:
2000Mbps (full duplex)

Network Cables

- 10BASE-T:
UTP Cat. 3, 4, 5 (100 m max.)
EIA/TIA-586 100-ohm STP (100 m max.)
- 100BASE-TX, 1000BASE-T:
UTP Cat. 5 (100 m max.)
EIA/TIA-568 100-ohm STP (100 m max.)

Flow Control

- IEEE 802.3x flow control per for full duplex
- Back pressure in half duplex

Full/half Duplex

- Full duplex only (1000Mbps)
- Full/half duplex (10/100Mbps)

Diagnostic LED Report

- 1000/100/10Mbps
- Full duplex

System Setup

IRQ

Allocated by system

I/O Address

Allocated by system

Environmental & Physical

Operating Temperature

0° to 40 °C

Storage Temperature

-25° to 55 °C

Operating Humidity

5% to 90% RH

Storage Humidity

5% to 90% RH

Emission

- FCC Class B
- CE Class B
- ICES-003

Network O.S. Support

- Microsoft Windows 98, NT 4.0, ME, 2000, XP, XP 64 Edition, Server 2003
- Novell NetWare Server 5.x, 6.x
- Novell Client for DOS
- Linux kernel 2.2.x, 2.4.x, 2.6.x
- Mac OS 10.2, 10.3, 10.4.X
- DOS ODIClient
- NDIS for DOS
- Free BSD 4.x, 5.0



Ordering Information

Copper Gigabit PCI Card

DGE-528T 10/100/1000Mbps PCI card

Optional Boot ROM

DGE-528R RPL and PXE remote boot ROM (PLLC type)

D-Link Worldwide Offices

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Europe (U. K.)	TEL: 44-20-8955-9000	FAX: 44-20-8955-9001	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
France	TEL: 33-1-30238688	FAX: 33-1-30238689	India	TEL: 91-022-26526696	FAX: 91-022-26528914
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Turkey	TEL: 0212-289-5659	FAX: 0212-289-7606
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Iran	TEL: 9821-8882-2613	FAX: 9821-8883-5492
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Pakistan	TEL: 92-21-454 8158	FAX: 92-21- 453 5103
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Egypt	TEL: 202-291-9035	FAX: 202-291-9051
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Finland	TEL: 358-10-309 8840	FAX: 358-10-309 8841	LatinAmerica	TEL: 56-2-5838-950	FAX: 56-2-5838-952
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Portugal	TEL: 351-21-8688493		South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Czech Republic	TEL: 420-(603)-276-589		Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099 #350
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-1188
			Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898