



Ph: 931-528-6518  
Fax: 931-528-7426  
sales@fluitek.com

SPECIFICATION SHEET

ELEMENT MODEL NUMBER.....	C 6022-3P3
ELEMENT TYPE.....	COALESCER
FILTRATION SELECTIVITY RATING (NOMINAL).....	0.5 MICRON
DIRECTION OF FLOW.....	INSIDE-->OUTSIDE
MAXIMUM FLOW.....	
OPERATING TEMPERATURE RANGE.....	225°F MAX
INITIAL DIFFERENTIAL PRESSURE RECOMMENDED....	
REPLACEMENT DIFFERENTIAL PRESSURE.....	25 PSID
MINIMUM ELEMENT COLLAPSE PRESSURE.....	78 PSID
CENTER TUBE.....	NONE
END CAPS.....	GLASS FILLED NYLON
JACKET.....	SOCK
HANDLE.....	NONE
GASKET.....	BUNA
MEDIA.....	PAPER/GLASS
ELEMENT OD.....	6.000
ELEMENT ID.....	3.250
ELEMENT LG.....	23.000
NO. OF ELEMENTS PER CARTON.....	6
WEIGHT PER CARTON.....	15.0

\*SINGLE OPEN END. 4272 SQ INCHES OF FILTER AREA