

# **HOSE & ACCESSORIES FIRE HOSE**

Model/Series No. 2901-2916 **SERIES** 

## **SPECIFICATIONS**

#### SINGLE JACKET HOSE

300 lb. ACCEPTANCE TEXT & 150 lb. SERVICE TEST -100% polyester jacket and synthetic rubber lining. Size as selected by model number.

600 lb. ACCEPTANCE TEST & 300 lb. SERVICE TEST -100% polyester jacket and synthetic rubber lining. Designed for more resistance to many acids, alkaline and other chemicals. Used where working pressures are higher than normal. Size as selected by model number.

#### **DOUBLE JACKET HOSE**

800 lb. ACCEPTANCE TEST & 400 lb. SERVICE TEST -100% polyester double jacket and synthetic rubber lining. Size as selected by model number.

#### **RACK AND REEL POLYFLEX HOSE**

500 lb. ACCEPTANCE TEST & 250 lb. SERVICE TEST -100% synthetic jacket and extruded 100% synthetic lining. Size as selected by model number.

|--|

SINGLE JACKET HOSE	PRODUCT OPTIONS		
□ 2901	LENGTHS:		
□ 2902	<b>5</b> 0'		
<b>2903</b>	☐ 75' ☐ 100'		
<b>2904</b>	<b>1</b> 100		
<b>2905</b>	VARIATIONS:		
□ 2906	-N Neoprene lining		
DOUBLE JACKET HOSE	OPTIONS:		
<b>2911</b>	☐ -U/L Label		
<b>2912</b>	☐ -U/L Label 300 TEST (2915 & 2916 Models Only)		
<b>2913</b>	<ul><li>☐ Neoprene Impregnation</li><li>☐ Hypalon Impregnation</li></ul>		
<b>2914</b>	— ·· · · ·		
	THREADS:		
RACK AND REEL POLYFLEX HOSE	☐ N.S.T. ☐ Other		
<b>2915</b>			
□ 2916			

100% SYNTHETIC totally immune to mildew and rot, never needs drying. 100% POLYESTER will not mildew or decay with age. Resistant to many acids.

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.

Date: 04/11/16













### POTTER ROEMER/FIRE PRO

Headquarters: New York (800) 526-4592 P.O. Box 3527 Chicago (800) 547-3473 City of Industry, CA Atlanta (800) 762-0542 Miami (866) 961-3473 91744 U.S.A. Los Angeles Area Dallas (866) 644-3473 800-366-3473 626-855-4890

MODEL 2901 (Shown)

www.potterroemer.com

Also in:

## **MODEL SELECTION**

Model No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling			
	Single Jacket Hose 300 lb. Test						
2901	1-1/2"	1-1/2"	1-3/4"	2934			
2902	2-1/2"	2-1/2"	2-13/16"	2936			
Single Jacket Hose 600 lb. Test							
2903	1-1/2"	1-1/2"	1-3/4"	2934			
2904	1-1/2"	1-3/4"	1-15/16"	2942			
2905	1-1/2"	2"	2-5/16"	2942 - 2-5/16			
2906	2-1/2"	2-1/2"	2-13/16"	2936			



Model No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling		
	Double Jacket Hose 800 lb. Test					
2911	1-1/2"	1-1/2"	1-15/16"	2938		
2912	1-1/2"	1-3/4"	2-1/8"	2942 - 2-1/8		
2913	1-1/2"	2"	2-9/16"	2942 - 2-9/16		
2914	2-1/2"	2-1/2"	3"	2944		



Model No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling	
Rack and Reel Polyflex Hose 500 lb. Test					
2915	1-1/2"	1-1/2"	1-11/16"	2930	
2916	2-1/2"	2-1/2"	2-13/16"	2936	



Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer-Fire Pro, Member of Morris Group International The Please visit potterroemer.com for most current specifications.















## POTTER ROEMER/FIRE PRO

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473

www.potterroemer.com