

UFX-20/20-2 F6+F8 IE3

Filter units with acoustic insulation. fitted with double-inlet fans and with different filtering phases. depending on model



Characteristics:

- Acoustically insulated structure.
- Belt actuation.
- F6 + F8. F7 + F9 and G4 + F6 filters. depending on selected model.
- Pre-filter option. plus two filtering phases.
- Inspection hatch and easy access for cleaning.
- Pressure connections for filter control.



Construction:

- Galvanised sheet steel structure with acoustic insulation.
- Impeller with forward-curved blades. made of galvanised sheet steel.
- Cable gland for cable entry.
- Built-in support bench.

Motor:

- Class F motors with ball bearings and IP55 protection.
- IE3 efficiency motors for powers equal to or greater than 0.75kW except single-phase. 2-speed and 8-pole.
- Three-phase 230/400V-50Hz (up to 4 kW) and 400/690V-50Hz (powers higher than 4 kW).
- Maximum temperature of air to be carried: -20°C + 60°C.

Finish:

- Corrosion-proof galvanised sheet steel.

DIMENSIONS

A	B	C	D1	D2	B1	H	H1	G	J
2515	1236.5	1192	1123	1095	80	1855	770	2635	1194

Dimensions without explicitly defined units are shown in millimeters (mm)

