

18.605 G

Submersible OEM-Pressure Transmitter

Applications

- ▶ level measurement in water and fuel oil tanks

Characteristics

- ▶ piezoresistive stainless steel sensor
- ▶ accuracy 0.5 % FSO according to IEC 60770
- ▶ nominal pressure ranges from 0 ... 1 mH₂O up to 0 ... 10 mH₂O



Technical Data



Input pressure range	
Nominal pressure gauge [bar]	0.1 0.25 0.4 0.6 1
Level [mH ₂ O]	1 2.5 4 6 10
Overpressure [bar]	1 1 1 3 3
Burst pressure ≥ [bar]	1.5 1.5 1.5 5 5
Vacuum resistance	unlimited

Output signal / Supply	
Standard	2-wire: 4 ... 20 mA / V _S = 8 ... 32 V _{DC}
Option 3-wire	3-wire: 0 ... 10 V / V _S = 14 ... 30 V _{DC}
	3-wire ratiometric: 10 ... 90 % of V _S / V _S = 2.7 ... 5 V _{DC}

Performance	
Accuracy ¹	P _N > 160 mbar: ≤ ± 0.5 % FSO P _N ≤ 160 mbar: ≤ ± 1 % FSO
Permissible load	2-wire: R _{max} = [(V _S - V _{S min}) / 0.02 A] Ω 3-wire: R _{min} = 10 kΩ
Influence effects	supply: 0.05 % FSO / 10 V load: 0.05 % FSO / kΩ
Response time	2-wire: ≤ 10 msec 3-wire: ≤ 3 msec
Long term stability	≤ ± 0.2 % FSO / year at reference conditions
Measuring range	1 kHz

¹ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)

Thermal effects (Offset and Span) / Permissible temperatures	
Thermal error	≤ ± 0.3 % FSO / 10 K in compensated range 0 ... 70 °C
Permissible temperatures	medium / electronics / environment / storage: -10 ... 70 °C

Electrical protection	
Short circuit protection	permanent 3-wire ratiometric: none
Reverse polarity protection	no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	10 g, 25 Hz ... 2 kHz according to DIN EN 60068-2-6
Shock	100 g / 1 msec according to DIN EN 60068-2-27
Materials (media wetted)	
Housing	stainless steel 1.4301 (304)
Seals	FKM
Diaphragm	stainless steel 1.4435 (316 L)
Cable sheath	PVC (oil resistant)
Miscellaneous	
Weight	approx. 120 g (without cable) cable: 25 g / m
Cable length	3 m, 6 m, 9 m or 12 m; others on request
Suitable for following media	water, fuel oil
Current consumption	2-wire: max. 25 mA 3-wire ratiometric: typ. 1.5 mA 3-wire voltage: typ. 5 mA (short circuit current: max. 20 mA)
Ingress protection	IP 68
CE-conformity	EMC Directive: 2014/30/EU
Wiring diagrams	
2-wire-system (current)	3-wire-system (voltage)
Pin configuration	
Electrical connections	cable colours (IEC 60757)
Supply +	wh (white)
Supply -	bn (brown)
Signal + (only for 3-wire)	gn (green)
Shield	gnye (green-yellow)
Dimensions (in mm)	
<p>G1/4" DIN 3852 with PVC cable (with air tube)</p>	

© 2019 BD/SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code 18.605 G

18.605 G - - - - - - -

Input	[mH ₂ O]	[bar]																			
	1.0	0.1	1	0	0	0															
	2.5	0.25	2	5	0	0															
	4	0.4	4	0	0	0															
	6	0.6	6	0	0	0															
	10	1.0	1	0	0	1															
	customer		9	9	9															consult	
Pressure																					
		bar					B														
		mH ₂ O					M														
		customer					9													consult	
Output																					
	4 ... 20 mA / 2-wire						1														
	0 ... 10 V / 3-wire						3														
	10 ... 90% of V _S / 3-wire ratiometric						R														
	customer						9													consult	
Accuracy																					
P _N > 160 mbar:	≤ ± 0.5 % FSO						5														
P _N ≤ 160 mbar:	≤ ± 1 % FSO						8														
	customer						9													consult	
Electrical connection																					
	PVC-cable						1														
	customer						9													consult	
Cable length																					
	3 m						0	0	3												
	6 m						0	0	6												
	9 m						0	0	9												
	12 m						0	1	2												
	customer						9	9	9												
Mechanical connection																					
	G1/4" DIN 3852									3	0	0									
	customer									9	9	9								consult	
Seals																					
	FKM											1									
	customer											9								consult	
Special version																					
	standard																		0	0	0
	customer																		9	9	9
																					consult

© 2016 BD|SENSORS GmbH - The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

