

**Volumenstrom [m<sup>3</sup>/h], Baureihe IL / ILI**  
**Air current capacity [m<sup>3</sup>/h], type IL / ILI**  
**Courant en volumes [m<sup>3</sup>/h], version IL / ILI**  
**Caudal volumétrico [m<sup>3</sup>/h], variante de serie IL / ILI**  
**Portata in volume[m<sup>3</sup>/h], serie IL / ILI**

**IL**

| <b>Bg</b><br><b>Frame size</b><br><b>HA</b><br><b>Tamaño</b><br><b>mod.</b> | 400V 50Hz        | 460V 60Hz        | 400V 50Hz        | 460V 60Hz        | 400V 50Hz        | 460V 60Hz        |
|---|------------------|------------------|------------------|------------------|------------------|------------------|
|   | 3 ~ Y<br>2-polig | 3 ~ Y<br>2-polig | 3 ~ Y<br>4-polig | 3 ~ Y<br>4-polig | 3 ~ Δ<br>4-polig | 3 ~ Δ<br>4-polig |
| 63  | 54               | 69               | /                | /                | /                | /                |
| 71  | 78               | 98               | /                | /                | /                | /                |
| 80  | 127              | 148              | /                | /                | /                | /                |
| 90  | 200              | 240              | 109              | 130              | /                | /                |
| 100   | 260              | 310              | 141              | 164              | /                | /                |
| 112   | 337              | 411              | 168              | 200              | /                | /                |
| 132   | 532              | 633              | 278              | 330              | /                | /                |
| 160   | 935              | 1068             | 507              | 607              | /                | /                |
| 180   | 1145             | 1270             | 604              | 680              | /                | /                |
| 200   | 1263             | 1450             | 640              | 760              | /                | /                |
| 204   | /                | /                | 990              | 1163             | 1051             | 1271             |
| 225   | /                | /                | 1123             | 1295             | 1180             | 1415             |
| 249   | /                | /                | 1350             | 1570             | 1450             | 1732             |
| 250   | /                | /                | 1666             | 1885             | 1839             | 2190             |
| 280   | /                | /                | 2116             | 2461             | 2404             | 2840             |
| 315   | /                | /                | 2662             | 2943             | 2848             | 3350             |

mit b-seitigem Referenzlagerschild /with bearing shield of reference on side b /avec de référence flasque  
 latérale b / placa de referencia en el lado b /con targhetta cuscinetti di riferimento lato b

**Volumenstrom [m<sup>3</sup>/h], Baureihe IL / ILI**  
**Air current capacity [m<sup>3</sup>/h], type IL / ILI**  
**Courant en volumes [m<sup>3</sup>/h], version IL / ILI**  
**Caudal volumétrico [m<sup>3</sup>/h], variante de serie IL / ILI**  
**Portata in volume[m<sup>3</sup>/h], serie IL / ILI**

## ILI

| Bg<br>Frame size<br>HA<br>Tamaño<br>mod. | 400V 50Hz        | 460V 60Hz        | 400V 50Hz        | 460V 60Hz        | 400V 50Hz        | 460V 60Hz        |
|--|------------------|------------------|------------------|------------------|------------------|------------------|
|  | 3 ~ Y<br>2-polig | 3 ~ Y<br>2-polig | 3 ~ Y<br>4-polig | 3 ~ Y<br>4-polig | 3 ~ Δ<br>4-polig | 3 ~ Δ<br>4-polig |
| 63                                       | 54               | 69               | /                | /                | /                | /                |
| 71                                       | 78               | 99               | /                | /                | /                | /                |
| 80                                       | 128              | 151              | /                | /                | /                | /                |
| 90                                       | 216              | 258              | /                | /                | /                | /                |
| 100                                      | 278              | 328              | /                | /                | /                | /                |
| 112                                      | 355              | 418              | 180              | 210              | /                | /                |
| 132                                      | 550              | 650              | 290              | 340              | /                | /                |
| 160                                      | 980              | 1160             | 520              | 620              | /                | /                |
| 180                                      | 1200             | 1379             | 619              | 695              | /                | /                |
| 200                                      | 1324             | 1575             | 656              | 776              | /                | /                |
| 204                                      | /                | /                | 1062             | 1237             | 1103             | 1313             |
| 225                                      | /                | /                | 1283             | 1467             | 1337             | 1580             |
| 249                                      | /                | /                | 1457             | 1714             | 1532             | 1832             |
| 250                                      | /                | /                | 1672             | 1919             | 1764             | 2097             |
| 280                                      | /                | /                | 2170             | 2472             | 2319             | 2760             |
| 315                                      | /                | /                | 2560             | 2935             | 2747             | 3274             |

mit b-seitigem Referenzlagerschild /with bearing shield of reference on side b /avec de référence flasque  
 latérale b / placa de referencia en el lado b /con targhetta cuscinetti di riferimento lato b