



Model	A	B	C	D
VENTILOR 20/8 M - 20/8 AR	280	280	94	30
VENTILOR 25/10 AR	335	335	128	33

VENTILOR

AXIAL FAN GLASS MOUNTING

- Axial fans to extract air directly outside;
- Glass, double glass or panel mounting up to 50 mm;
- Optional kit for wall and double glass installation;
- Slow and quiet motion of shutter; manual opening through Pull Cord (20/8 M model);
- Operating indicator light (except 20/8M model);

- Rain proof IPX4 external grille;
- On/Off, reversible airflow (extraction/intake) and 5 speed through optional RG 5 AR controller;
- Careful selection of materials: grilles in white ABS and body in polystyrene;
- In accordance with Standard EN 60335-2-80.



POSITIONING

- Glass mounting - Wall mounting

DATI TECNICI

Model	Code	Ø hole (mm)	Voltage (V)	Frequency (Hz)	Flow rate (m ³ /h)	Max press. (mm H ₂ O)	Max press. (Pa)	Power (W)	Noisiness dB(A) _{1m}	Weight (Kg)
VENTILOR 20/8 M	0018800	225-235	220-240	50/60 Hz	450	12	118	50	58	2,4
VENTILOR 20/8 AR	0019000	225-235	220-240	50/60 Hz	450	12	118	50	58	2,4
VENTILOR 25/10 AR	0019200	275-285	220-240	50/60 Hz	750	6	59	60	45	5,6

FLOW CHARTS

