

STRAINER FOR FLANGE**CA 3241CREPINOX****APPLICATION**

General use : for water distribution and draining.

GENERAL CHARACTERISTICS

From DN50 to DN300.
For flange connection.
Mesh 6 mm
With bolting.

DIMENSIONS

DN		H	ØA	ØK	ØD	n x ØM	f	Weight (kg)
mm	inch							
50	2"	77	91	125	158	4 x Ø9	2,5	0,426
65	2"1/2	100	127	145	180	4 x Ø9	2,5	0,746
80	3"	125	127	160	180	4 x Ø9	2,5	0,858
100	4"	142	164	183	212	4 x Ø9	2,5	1,096
125	5"	166	180	210	240	4 x Ø9	2,5	1,432
150	6"	200	212	240	268	4 x Ø9	2,5	1,796
200	8"	300	255	285	318	4 x Ø9	2,5	2,527
250	10"	380	330	362	395	4 x Ø9	2,5	4,500
300	12"	410	380	415	445	4 x Ø9	2,5	5,386

WORKING CONDITIONS

Maximum working conditions : -20°C / +200°C

Maximum working pressure: 16 bar

STANDARDS

Fabrication according to ISO 9001 :2000
Flanged connection: ISO PN10/16 from DN50 to DN150
ISO PN16 from DN200 to DN300..

