

Soft PVC hose with embedded galvanized steel spiral for suction and delivery of food liquids. Heavy duty version.



 SMOOTH SURFACE \*\*\*\*\*


 FLEXIBILITY \*\*\*\*\*

 ABRASION RESISTANCE \*\*\*

 TEMPERATURE RANGE  
-5 °C 65 °C

 CHEMICAL RESISTANCE  
Table PVC

 CRUSHING RESISTANCE \*\*\*

 FOR FOOD  
Suitable for contact with foodstuff according to the declaration of conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H <sub>2</sub> O	working press. at 23° r:1,3 bar	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
10	3/8	10	16	9.5	8	24	20	3	0.8	6.5	right	155	60	On demand
12		12	18	9.5	8	24	25	3	0.8	7	right	180	60	On demand
14		14	20	9.5	8	24	30	3	0.8	7.5	right	200	60	On demand
16	5/8	16	22	9.5	8	24	35	3	0.8	7.5	right	225	60	On demand
18		18	24.5	9.5	7	21	40	3.25	1	8	right	280	60	On demand
20		20	27	9.5	6	18	50	3.5	1	8	right	340	60	On demand
22	7/8	22	29	9.5	6	18	55	3.5	1	8.5	right	360	60	On demand
25	1	25	33	9.5	6	18	60	4	1.4	13.5	right	510	60	On demand
30		30	39.5	9.5	5	15	70	4.75	1.4	14.5	right	680	60	On demand
32	1 1/4	32	41.5	9.5	5	15	75	4.75	1.4	14.5	right	730	60	On demand
35		35	44	9.5	5	15	80	4.5	1.4	14.5	right	730	60	On demand
38	1 1/2	38	49	9.5	5	15	90	5.5	1.6	15	right	950	30	On demand
40		40	53	9.5	5	15	100	6.5	2	17	right	1220	30	On demand
45	1 3/4	45	58	9.5	5	15	110	6.5	2	18	right	1400	30	On demand
50	2	50	64	9	5	15	125	7	2	18	right	1600	30	In stock
60		60	74	9	5	15	140	7	2.5	20	right	2050	30	On demand
63	2 1/2	63	77	9	4	12	150	7	2.5	20	right	2250	30	On demand
70		70	86	9	4	12	180	8	2.5	20	right	2600	30	On demand
75		75	91	9	4	12	200	8	2.5	17	right	2850	30	On demand
80		80	96	9	3	9	220	8	2.5	17.5	right	3150	30	On demand
90	3 1/2	90	107	9	3	9	260	8.5	3	18	right	3750	30	In stock
100		100	118	9	3	9	300	9	3	18.5	right	4400	30	On demand
105		105	122	9	2	6	310	8.5	2.5	19.5	right	4000	20	On demand
110		110	128	9	3	9	320	9	3	19	right	4650	20	On demand
120		120	138	9	2	6	340	9	3	19.5	right	5200	20	On demand
125		125	144	9	2	6	350	9.5	3	20	right	5400	20	On demand
150		151	170	9	2	6	450	9.5	3	18	right	7200	20	On demand
203	8	202	224	9	2	6	900	11	3	19.5	right	9900		On demand