

ity to ensure that the...  
ity to regulate the noise level using an adequate device respecting norms currently in effect.  
of anti-spark execution fans must conform to the norms of the respective country (ref. Comets VDMA 24189  
appropriate means must be used; fans in cardboard boxes must be lifted from the base of the box.  
cardboard boxes, stacking limits must be respected (i.e. sizes 160 to 315: max 4 units, sizes 355 to 450: max.  
max 2 units).

ation, the user must:  
ts are not in contact with stationary parts.  
cident-prevention precautions have been taken (e.g. keeping ones distance from moving parts).  
r's rotation direction corresponds to the direction of the arrow found on the fan casing.  
e first 500 hours of operation ensuring that they have been tightened to guarantee stability in assembled comp  
no operating abnormalities such as excessive vibrations or noise. In these instances it is necessary to stop



**comefri** s.p.a.

33010 MAGNANO IN RIVIERA (UD) ITALIA

TEL. 0432 788111

FAX 0432 783378



CODE

15601000

ABSORBED POWER

KW MAX

13,5

Q AT 20°C

Kg/m<sup>3</sup>

1,2

SERIAL NO.

6 0334 36

TYPE

TLZ 560 A

SPEED

RPM

1200

TEMPERATURE

°C MAX

80

YEAR OF CONSTRUCTION

1996

